



MODEL	TRANSMISSION			ENGINE						PTO								
	Synchronous transmission with direction change control	Synchronous transmission with Powershuttle	2-stage Powershift with Powershuttle	Nominal power ECE R120 ¹⁾ [kW (hp)]	Common rail, 2-valve diesel engine, turbocharger with intercooling / stage 3					Electro-hydraulic switchable								
	12 forward and reverse gears	12 forward and reverse gears	24 forward and reverse gears		Nominal engine speed [rpm]	Max torque ECE R120 ¹⁾ [Nm @ rpm]	Torque rise as per OECD [%]	Engine capacity / Number of cylinders [cm ³]	Fuel tank capacity [l]	PTO speed [rpm]				at engine speed of [rpm]			ground speed PTO	
	20 forward and 20 reverse-gears (Kompakt S), 20 forward and 12 reverse-gears (Kompakt) with creeper gearbox	20 forward and 20 reverse-gears with creeper gearbox								540	540/540E	540/1,000	540/540E/1,000	1,950	1,950/1,550	1,950/1,950		1,950/1,550 1,950
4055 KOMPAKT S	●	○	—	41 / 56	2,300	221 @ 1,400	35	3,200 / 4	90	●	○	—	—	●	○	—	—	○
4065 KOMPAKT S	●	○	—	48 / 65	2,300	260 @ 1,400	35	3,200 / 4	90	●	○	—	—	●	○	—	—	○
4085 KOMPAKT	●	○	○	63 / 86	2,300	351 @ 1,500	34	3,400 / 4	115	●	—	○	○	●	—	○	○	●
4095 KOMPAKT	●	○	○	73 / 99	2,300	407 @ 1,500	34	3,400 / 4	115	●	—	○	○	●	—	○	○	●
4105 KOMPAKT	●	○	○	79 / 107	2,300	444 @ 1,500	35	3,400 / 4	115	●	—	○	○	●	—	○	○	●

MODEL	HYDRAULICS				4WD & STEERING		TYRES ³⁾	WEIGHT* WITH CAB AND 4WD	CAB	
	MHR control (mechanical hitch regulation)	EHR control (electronic hitch regulation)	Max. capacity Standard / Optional [l/min]	Max. lift capacity / constant lift capacity at ends of lower linkages OECD [kg]	Max. number of mechanical remote valves rear / mid mounted	Electro-hydraulic 4WD engagement	Wheel lock angle [°]	Standard tyres*	Weight empty [kg]	
							Turning circle [m]			
4055 KOMPAKT S	●	—	48 / -	2,800 / 2,100	3 / 2	●	55°	14.9R20	2,800	Spacious cab with flat cab floor, comfortable passenger seat, adjustable driver's seat, efficient heating and air conditioning, best all-round vision, exhaust on A pillar, new design of heating and ventilation system for highest level of comfort, slanted engine hood, tilting roof window, powerful floodlight package, operator console on right with ergonomically placed controls.
4065 KOMPAKT S	●	—	48 / -	2,800 / 2,100	3 / 2	●	3.75	16.9R30	4,800	
4085 KOMPAKT	○	● only in combination with 24 x 24	48 / 64	3,900 / 3,200	3 / 2	●	55°	14.9R20 - 360/70R20	3,600	Spacious cab with flat cab floor, comfortable passenger seat, adjustable driver's seat, cab suspension, noise level in cab 76 dB(A), efficient heating, wide windscreen, best all-round vision, exhaust on A pillar, slanted engine hood, tilting roof window, powerful floodlight package, operator console on right with ergonomically placed controls.
4095 KOMPAKT	○	● only in combination with 24 x 24	48 / 64	3,900 / 3,200	3 / 2	●	5.3	16.9R30 - 420/70R30	6,200	
4105 KOMPAKT	○	● only in combination with 24 x 24	48 / 64	3,900 / 3,200	3 / 2	●	5.3	16.9R30 - 420/70R30	6,200	

● Standard ○ Optional — Not available *) To comply with legislation and specifications in your country 1) ECE R120 complies with ISO 14396 or 2000/25/EC or EG 97/68 2) With standard tyres 3) Other tyres available on request